

# AXIS

## 5MM AXIS™

Heart-stopping penetration.  
The hands-down proven micro-diameter all-carbon arrow.

- 5mm micro-diameter carbon-composite fibers
- Pre-installed 5mm (X) nocks
- 5mm (X) HIT 8-32 inserts
- Straightness  $\pm 0.003"$

### INCLUDED



5mm (X) HIT® Insert  
(16 grains)



5mm (X) Nock™  
(9 grains)

### SOLD SEPARATELY



8-32 Multi Point  
(75, 85, 100, & 125 grains)



8-32 RPS Point  
(50, 60, 70, 80, 90, 100, 110, & 125 grains)



Deep Six™ Steel Field Points  
(100-125 grains)



5mm (X) Deep Six™ Steel RPS Insert  
(25 grains)



5mm Brass X HIT® Break-Off 8-32 Insert  
(Adjustable to 75-50 grains)

*NEW Axis Match Grade  
 $\pm 0.001$  straightness  
now available.*

SIZE	SHAFT WEIGHT	SPINE @ 28" SPAN	STOCK LENGTH	RPS POINT	BROADHEAD ADAPTER RING	O.D.
	GPI	Deflection in Inches	Inches	O.D. Inches	Size (5 grains)	Inches
700	6.1	0.700	31.5	17/64	BAR3	0.245
600	7.2	0.600	30.5	17/64	BAR3	0.253
500	8.1	0.500	31	17/64	BAR3	0.258
400	9.0	0.400	31.5	17/64	BAR4	0.264
340	9.5	0.340	32	9/32	BAR5	0.267
300	10.7	0.300	32.5	9/32	BAR6	0.275
260	11.5	0.260	34*	9/32	BAR6	0.280

\*Fletched 6-pack arrows are 32" max stock length.

